

RX Series Upright Rammers

Simply Powerful

Ingersoll-Rand Upright Rammers

Engineered to compact materials ranging from mixed and cohesive soils to heavy clays, the RX Series of upright rammers provide compaction solutions for a wide array of applications. All Ingersoll-Rand light compaction equipment is manufactured with the highest quality and backed by our service and reputation. The RX Series of rammers are jobsite tough and charged with industry leading impact forces to conquer your everyday challenges.



PRODUCT SPECIFICATIONS

KEY FEATURES

■ **Industry-leading impact forces:** To achieve desired compaction levels while using maximum lift thickness.

■ **4-cycle Honda engine:** Eliminates need to mix gas and oil. More efficient operation and fuel economy.

■ **Self-balanced design:** Greater maneuverability and maximum control around jobsite obstacles.

■ **4-point isolation and vibration-reducing grip:** Minimizes operator fatigue and prolongs the life of rammer components.

IR MODEL	RX-264H	RX-304H	RX-344H
DIMENSIONS			
Overall Length in (mm)	26.6 (675)	26.6 (675)	26.6 (675)
Overall Width in (mm)	15.2 (385)	18.3 (466)	18.3 (466)
Overall Height in (mm)	43.3 (1100)	43.3 (1100)	43.9 (1115)
Foot Size (w x l) in (mm)	9 x 13 (230 x 330)	11 x 13 (270 x 330)	11 x 13 (270 x 330)
Operating Weight lb (kg)	127 (58)	156 (71)	157 (72)
PERFORMANCE			
Impact Force lb (kN)	2,600 (11.2)	3,000 (13.4)	3,400 (15.1)
Blows Per Minute	600-750	600-750	600-750
Travel Speed fpm (mpm)	39-46 (12-14)	39-46 (12-14)	39-46 (12-14)
Area Capacity Per Hr. sq ft (sq m)	2,100 (195)	2,530 (235)	2,530 (235)
Recommended Compaction Depth in (mm)	18 (460)	21 (530)	24 (610)
ENGINE			
Type	Honda, 4-cycle	Honda, 4-cycle	Honda, 4-cycle
Model	GX100KRA2	GX120AR	GX120AR
Horsepower hp (kW)	3.0 (2.2)	4.0 (2.9)	4.0 (2.9)
Engine Speed rpm	4000	3600	3600
Fuel Tank Capacity qt (L)	2.6 (2.5)	2.6 (2.5)	2.6 (2.5)
FOOT OPTIONS		CPN	AVAILABLE ON:
Foot Size (w x l) in (mm)	6 x 13 (152 x 330)	58836552	RX-264H
Foot Size (w x l) in (mm)	8 x 13 (200 x 330)	58836974	RX-264H
Foot Size (w x l) in (mm)	9 x 13 (230 x 330)	59106369	RX-304H and RX-344H

Specifications are subject to change without notice.

Powerful Performance

Each rammer comes equipped with a rugged and reliable, 4-cycle Honda engine with recoil start engineered to provide years of dependable operation. Oil-splash lubrication reduces the need for daily greasing while ensuring continuous protection of all internal parts. Engine speed remains constant through ratchet-type throttle control. The engine cover protects the operator and machine, yet can be easily removed to allow access to all service components.

Designed for safe and efficient use, the comfortable operator handle features a vibration-reducing padded grip and has an integrated lifting bail, protecting the engine and other components from damage. Impact force is applied to material being compacted by a durable wooden foot, reinforced with a heavy steel plate for extended life.

The RX Series' low profile, lightweight design and low center of gravity make the Ingersoll-Rand line-up of rammers your best choice for backfilling and narrow trench compaction.

